

865 Block

BLOCKING AND EXOTIC WOOD PRIMER

PRODUCT DESCRIPTION

Primer (containing solvents) to use before application of Eurocol parquet lacquers. Blocks against wood components and wax residues which might cause problems with lacquer bonding and discoloration. Especially for exotic wood, smoked oak. Ideal for renovation of old flooring. Hazardous material: Please consider security advices! For indoor use only.

PRODUKTVORTEILE

Blocking against different wood components and against wax remains in the renovation of old floor.

Ready for processing, lightweight, warm-toned accentuation and reduces the side-bonding. Reduces as well the entry of moisture from water-based paints in the renovation of the entire surface of glued multilayer parquet.

APPLICATION



For priming of:

- Parquet floors, especially parquet flooring from exotic wood
- Parquet in the context of renovations, in which wax or care agent residues are suspected
- old, clean-cut multi-layer parquet flooring

TECHINICAL DATA

Base

Synthetic Polymer

Colour

yellowish

Density

ca. 0,82 g/cm³

Consistency

low viscosity

Cleaner

Solvent

Proccession conditions

non below . 15 °C on the subfloor, minimum. 18°C material- and room temperature, 35-75% relative humidity, recommended <65%

Application

large brush or roller

Consumption

ca. 100 g/m² per coat , (ensure defect-free barrier)

Drying time

Minimum 12, maximum 24 hours

Permitted shelf-life

Use within 12 months in original packing, opened products to be used as soon as possible

Storage conditions

packing to be tightly closed at a dry place, temperature (5-30 °C)

Sensitive to frost

no

865

Europrimer Block

Code acc. to GHS	See safety data sheet	
Environmental protection	GISCODE:	G 1
	DGNB:	VOC 87 %,
	LEED:	VOC 719,9 g/l
	DecoPaint EU/2004/42:	Kat. A/h/Lb: 750 g/l (2010)

FLOOR PREPARATION

The surface of the floor needs to be clean, free of oil, wax, silicon and other residues which negatively influence the bonding power. After rough sanding (grit: 26, 60,80), the joints up to 2 mm width are to be closed 8802 Eurofiller Wood Plus or 870 Eurofiller Wood mixed with sanding dust of grit 80. Allow it to dry for approx. 30 min and finely grind it again with a grit of 120.

INSTRUCTION FOR USE

- 865 blocking primer needs to be applied evenly with a solvent-resistant nylon roller (article 78902) on the grinded and cleaned wood floor.
- After the drying time of minimum 12 hrs. an application of Eurocol Aqua lacquers is required to be applied to the finish.
- Do not apply 865 Europrime Block with a spatula, as the consumption will not be enough and adhesion problems arise as well as it can penetrate wood components.
- Wood with high fat content (e.g. Lapacio) or very absorbent woods (steamed beech, maple, smoked, etc.) have to be treated with 2 coats of blocker.
- When renovating old parquet it is recommended to sand down to the original bare wood, the solvent in the 865 reduces the swelling of the parquet.
The intermediate drying time between two layers of 865 Europrime block is approx. 1 hour. Onto dense woods, always make a second application layer.
- The drying time will increase significantly over 12 hours with dense woods and /or higher humidity. Processing must be carried out at temperatures of at least 5 °C above dew point occur (questions regarding indoor climate to be asked at our technical department, the dew point is depended on room temperature and humidity. Condensation can occur on the surface of the primer if the temperature stated is exceeded, which may lead to milky and disturbed bonding. These types of surfaces should not be lacquered.
- Ensure constant air circulation while drying. Avoid direct sun and excessive air draught.
- ** Good grain accentuation can only be achieved on suitable wood (e.g. Oak).

SAFETY NOTE

- this product contains hazardous materials, please pay attention to the technical information and safety data sheet
- Do not use any other lacquering system other than the mentioned in this data sheet.

PACKING

10l disposable container (60/Pallet)

SPECIAL NOTE

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed.
This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work.

Forbo Eurocol Deutschland GmbH
August-Röbling-Straße 2
99091 Erfurt, Germany

Phone +49 361 7 30 41 0
Fax +49 361 7 30 41 90
info.erfurt@forbo.com
www.forbo-eurocol.de

Geschäftsführer: Rüdiger Beez
Handelsregister HRB 100351 Jena (D)
Ust.-IdNr. DE 811 178 280

865

Europrimer Block

The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content.

As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties.

Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use. This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

Technical information and Material Safety Data Sheets of concomitantly used installation materials must be followed carefully.

The products delivered by the manufacturer are for professional use only. Keep away from children.

The manufacturer's terms and conditions are binding.

Stand 24.05.2016
ersetzt Ausgabe vom 14.5.2012

Version Nr.:7
75603_865-HW01