

# 888

## UNIVERSAL MAINTENANCE

REGISTER 14

---

### PROPERTIES

---

- self-shining, cleaning and maintenance agent with water-soluble wax content
- does not create unwanted films of maintenance agents after several use
- fast drying
- dirt-repellent
- polishing not necessarily required for regular care
- gentle to the skin due to neutral pH-value
- pleasant odour
- no basic cleaning required on uncoated floors
- application in one single operation

---

### USAGE

---



FLOOR COVERING



PARQUET



CERAMIC TILES

- all water-proof floors such as sealed parquet, cork,
- PVC, linoleum, rubber, natural stone floor, artificial stone floor etc.

---

### TECHNICAL DATA

---

Base	water-soluble tensides and scents
Colour	transparent
Density	approx. 1,00 g/cm <sup>3</sup>
pH rating	7
Cleaning agent	water
Processing conditions	not below 15 °C on the subfloor, minimum 18°C material- and room temperature 35 - 75% relative air moisture, recommended <65%
Mode of application	wiper
Consumption	depending on dust
Permitted shelf-life	within approx. 36 months, opened packaging to be tightly closed and to be consumed as soon as possible
Storage condition	packaging to be tightly closed at a dry place, temperature: 5 - 30 °C,
Flammability	no
Code acc. to GHS	no
Environment/Work safety	GISCODE: GU 501 Contents according to EU regulation 648-2004 <ul style="list-style-type: none"><li>○ &lt; 5% none ionic surfactants</li><li>○ perfumes (CITRUS DULCIS),</li><li>○ preservative agents (METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE)</li></ul>

---

---

## INSTRUCTIONS FOR USE

---

- Intensive first care (construction cleaning):
- Please pour 100ml (related to the cleaning water) of 888 into 1 bucket (8l) of clean, cold water, polishing required after drying time of approx. 1 h, use an electric polisher (1 800 - 2 000 rpm.)
- Regular cleaning and maintaining:
- Please pour 40 ml of 888 into 8 l of clean cold water, no polishing required.
- Also possible to be used in cleaning machines, mixing ratio: 100 ml of 888 to 8 l clean cold water.
- For High Speed single-disc cleaning machines (approx. 1 500 rpm.):
- Polish the floor in order to get a dense protection film which is more durable.

---

## NOTE

---

- Relevant norms and regulations of the branch are to be respected.
- Outside Germany relevant national regulations are to be applied which have to be known by the user.

---

## PACKAGING

---

0,7 l nonreturnable package (12/bucket, 504/palette)  
5 l nonreturnable package (4/ bucket, 96/palette)

---

## SPECIAL NOTE

---

Any other application than those specified in this Technical Information requires our explicit approval. Otherwise no liability can be assumed.

The information contained in this product information has been based on experiences derived from laboratory and practical work. The great versatility of materials, many different processing and storage methods and local conditions beyond our control make it impossible to give guarantees for processing results. Therefore, customers are recommended to find the optimum for their particular application case by suitable self-made tests. The General Terms and Conditions of our company shall apply.

This Technical Information supersedes all other application data sheets and product information published before.

Last updated 2015-09-15  
Supersedes issue as of 2013-07-11

Version Nr.:07  
75222\_888-05  
Revision Formular TI: V05