
















Technical specifications




Create space 2 carpet tiles meet the requirements of EN 1307

tessera[®] create space 2

	Description	Tufted level loop pile carpet tile
	Dimensions	50cm x 50cm
	Total thickness	5.7mm ± 10%
	Pile height	3.0mm ± 0.5mm
	Collection size	15 colourways, 5m ² per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	100% ECONYL [®] /Altochroma polyamide 6
	Dye method	100% solution dyed
	Stitch density	245,440 per m ² ± 10%
	Pile weight	570 gsm ± 10%
	Total weight	4,085 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	Modified bitumen and polyester fleece. Also available in SOFTbac [®] secondary backing
	Castor chair use	BS EN 985 Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02 ≥5
	Dimensional stability	BS EN 986 ≤0.2%
	Creating Better Environments	
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources
	Recycled Content	Create space 2 contains over 50% recycled content by weight
	Indoor Air Quality	Create space 2 meets 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	Ska	Create space 2 meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes
	Guarantee	Create space 2 carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac [®]) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Monolithic, quarter turn, tessellated, half drop or non-directional

Create space 2 carpet tiles meet the requirements of EN 14041



	Reaction to fire	EN 13501-1	B _{fl} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Tessera Create Space 2 – Carpet Tiles (EN1307)

Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
A	A	A+	A	A	A+	✓

