

















Technical specifications




Mix carpet tiles meet the requirements of EN 1307

tessera[®] mix

	Description	Tufted multi-height loop pile carpet tile, Random lay. batchless	
	Dimensions	50cm x 50cm	
	Total thickness	5.9mm ± 10%	
	Pile height	3.0mm ± 0.5mm	
	Collection size	15 colourways, 5m² per box	
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Invista Antron® Lumena polyamide	
	Dye method	100% solution dyed	
	Stitch density	200,600 per m² ± 10%	
	Pile weight	650 gsm ± 10%	
	Total weight	4,165 gsm ± 10%	
	Primary backing	Polyester	
	Secondary backing	Modified bitumen and polyester fleece	
	Castor chair use	BS EN 985	Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02	≥5
	Dimensional stability	BS EN 986	≤0.2%
	Creating Better Environments		
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources	
	Recycled Content	Mix contains over 50% recycled content by weight	
	Indoor Air Quality	Mix meets 01350 Indoor Air Quality standard	
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor	
	Ska	Mix meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
	Guarantee	Mix carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Installation method	Random	

Mix carpet tiles meet the requirements of EN 14041

CE
EN 14041

	Reaction to fire	EN 13501-1	B _{f1} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Tessera Mix – Carpet Tiles (EN1307)

Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
A	A	A	B	A	A+	✓

