

## EL 0/U3 NP-HACCP blue FDA



Sketch of cross-section (not actual size)

### Applications

- Checkweighers
- Inspection systems
- Buffer conveyor
- Short center distances and wide belts, under-square belts

### Properties/Advantages

- Very good self-tracking properties. Tracks perfect when short center distances and wide belts
- Conditionally laterally stiff, semi elastic 1 ply hybrid fabric of polyester (special fabric construction), low risk of folding
- Production width 1,500 mm
- Mechanical fasteners are possible
- Tension between 1.5 % and 5.0 %. When belts are supplied with pretension no take-up necessary (cost saving)
- HACCP design
- FDA and EU compliant

### Basic technical data

Top face	Polyurethane, NP
Underside	Polyester fabric
Article no.	900458
d <sub>min</sub> [mm]	r = 3 mm
Total thickness [mm]	1.5
k <sub>1%</sub> relaxed [N/mm width]	0.6
Weight [kg/m <sup>2</sup> ]	1.35
Permitted operating temperature	-30 to +100 °C

Product Quick Info TR-900458-2 - 11/2020  
FMS - Reproduction of text or parts thereof only  
with our approval.  
Modifications reserved.

Forbo Siegling GmbH  
Lilienthalstraße 6/8, D-30179 Hannover  
Telefon +49 511 67 04 0, Fax +49 511 67 04 305  
www.forbo-siegling.com, siegling@forbo.com