

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: 355 LiquidDesign Finish - Komponent B**
- **Article number: 49355**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
FORBO Eurocol Deutschland GmbH  
August-Roebing-Str. 2  
D-99091 Erfurt  
Tel.: +49 (0)361 73041-0  
Fax: +49 (0)361 73041-92  
Website: <http://www.forbo-bonding.de>
- **Further information obtainable from:**  
Laboratory  
Ronny Dorna  
[Ronny.Dorna@forbo.com](mailto:Ronny.Dorna@forbo.com)
- **1.4 Emergency telephone number:** GGIZ +49-361-730730 (for Germany)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

- |                   |   |
|-------------------|---|
| Acute Tox. 4      | H332 Harmful if inhaled.                                |
| Skin Sens. 1      | H317 May cause an allergic skin reaction.               |
| STOT SE 3         | H335 May cause respiratory irritation.                  |
| -----             |   |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**  
aliphatic polyisocyanate  
hexamethylene diisocyanate
- **Hazard statements**  
H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 1)

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Safety data sheet available on request.

Restricted to professional users.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

**3.2 Chemical characterisation: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 160994-68-3	aliphatic polyisocyanate ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	50-100%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1	hexamethylene diisocyanate ⚠ Acute Tox. 3, H331; ⚠ Resp. Sens. 1, H334; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-<0.5%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

A person vomiting while laying on their back should be turned onto their side.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 2)

- Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)  
(possible HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Wear fully protective suit.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:**  
Do not allow to enter drains/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Dilute with plenty water.  
Allow to solidify. Pick up mechanically.  
Clean the affected area carefully; suitable cleaners are:  
Clean with water and soap. If possible, also wash with polyethylene glycol 400.  
Send for recovery or disposal in suitable receptacles.  
Do not seal receptacles gas-tight.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 3)

- Do not breathe vapour/aerosol.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from humidity and water.
- **Recommended storage temperature:** +10 °C - +30 °C
- **Storage class:** 12
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**822-06-0 hexamethylene diisocyanate**

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Recommended filter device for short term use:**

Combination filter A-P2

Filter A1

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.5$  mm

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

· **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic

· **pH-value:** Not applicable.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

· **Flash point:** Undetermined.

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** Undetermined.

· **Decomposition temperature:** Undetermined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

· **Vapour pressure:** Not determined.

· **Density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Undetermined.

· **Solvent content:**

VOC (CE) Not applicable.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

Trade name: 355 LiquidDesign Finish - Komponent B

(Contd. of page 5)

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions**
  - Reacts with alcohols.
  - Reacts with amines.
  - Reacts with water.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
  - Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

**160994-68-3 aliphatic polyisocyanate**

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

**822-06-0 hexamethylene diisocyanate**

Oral	LD50	738 mg/kg (rat)
------	------	-----------------

Dermal	LD50	593 mg/kg (rat)
--------	------	-----------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** not tested
- **Serious eye damage/irritation** not tested
- **Respiratory or skin sensitisation**
  - May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
  - May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**160994-68-3 aliphatic polyisocyanate**

LC50/96h	28.3 mg/l (zebrafish ( <i>Brachydanio rerio</i> )) (OECD 203)
----------	---

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 6)

EC50/48h >100 mg/l (*Daphnia magna*) (OECD 202)

EC50/72h >77.4 mg/l (*Scenedesmus suspicatus*)

**822-06-0 hexamethylene diisocyanate**

LC50/96h >82.8 mg/l (zebrafish (*Brachydanio rerio*)) (OECD 203)

EC50/48h >89.1 mg/l (*Daphnia magna*) (OECD 202)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Behaviour in sewage processing plants:**

Type of test	Effective concentration	Method	Assessment
<b>160994-68-3 aliphatic polyisocyanate</b>			
EC50/3h	>10000 mg/l (activated sludge)	(OECD 209)	
<b>822-06-0 hexamethylene diisocyanate</b>			
EC50/3h	842 mg/l (activated sludge)	(OECD 209)	

· **Type of test** Effective concentration Method Assessment

**160994-68-3 aliphatic polyisocyanate**

EC50/3h >10000 mg/l (activated sludge) (OECD 209)

**822-06-0 hexamethylene diisocyanate**

EC50/3h 842 mg/l (activated sludge) (OECD 209)

- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Harmful to aquatic organisms  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- |  |      |
|--|------|
| · <b>14.1 UN-Number</b>                  |      |
| · <b>ADR, ADN, IMDG, IATA</b>            | Void |
| · <b>14.2 UN proper shipping name</b>    |      |
| · <b>ADR, ADN, IMDG, IATA</b>            | Void |
| · <b>14.3 Transport hazard class(es)</b> |      |
| · <b>ADR, ADN, IMDG, IATA</b>            |      |
| · <b>Class</b>                           | Void |

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 7)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
· <b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed. (94/33/EC)  
Employment restrictions concerning pregnant and lactating women must be observed. (92/85/EC)
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Laboratory
- **Contact:**  
Dr. Amina Chnirheb  
Amina.Chnirheb@forbo.com

(Contd. on page 9)

GB



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 08.09.2017

Version number 2

Revision: 08.09.2017

**Trade name: 355 LiquidDesign Finish - Komponent B**

(Contd. of page 8)

**· Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*SVHC: Substances of Very High Concern*

*vPvB: very Persistent and very Bioaccumulative*

*Acute Tox. 3: Acute toxicity – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Resp. Sens. 1: Respiratory sensitisation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**· \* Data compared to the previous version altered.**

GB