



Technical specifications

Marmoleum soul

Meets the requirements of		EN-ISO 24011*
	Total thickness	EN ISO 24346 2.5 mm
Surface finish		Topshield pro
	Collection size	5
	Domestic use	EN ISO 10874 Class 23 (heavy)
	Commercial use	EN ISO 10874 Class 34 (very heavy)
	Light industrial use	EN ISO 10874 Class 43 (heavy)
	Roll width	EN ISO 24341 2.0 m
	Roll length	EN ISO 24341 ≤ 33 m1
	Total weight	EN ISO 23997 2900 g/m ²
	Castor chair continuous use	ISO 4918 Pass
	Residual indentation <i>Typical value</i>	EN ISO 24343-1 ≤ 0.15 mm ~ 0.08 mm
	Colour fastness to light ¹	EN ISO 105-B02 method 3 ≥ 6 (0001 origin ≥ 4) ¹
	Indoor air emissions: TVOC after 28 days	EN 16516 ≤ 0.01 mg/m ³
	Bacteriostatic properties ²	Marmoleum has natural bacteriostatic properties which are confirmed by independent laboratories, even against MRSA bacteria.
	Resistance to chemicals	EN ISO 26987 Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Cigarette resistance	EN 1399 There is no melting of the surface by cigarettes. Marks left on Marmoleum as a result of stubbed-out cigarettes can be removed.
	Flexibility	EN-ISO 24344 ø 40 mm
	Acoustical impact noise reduction	EN ISO 717-2 ≤ 5 dB
Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact.
	Creating better environments	Marmoleum is climate positive cradle to gate ² . Every m ² installed contributes to regenerating Australia's bushland and biodiversity through our partnership with Carbon Positive Australia (not as an offset program but rather as regeneration).
Natural materials		Marmoleum soul is a bio-based floor made with up to 99% natural ingredients (e.g. linseed oil, rosin, wood flour and jute). Marmoleum contains PEFC certified wood flour.
		Marmoleum is free of PVC, PET, synthetic rubber and plasticizers.
	Recycled content	Marmoleum contains ingredients derived from recycled sources, which are a combination of post-industrial, post-installation and post-consumer streams of both flooring and non-flooring Marmoleum products. Marmoleum sheet installation off-cuts and post-consumer used flooring are recyclable.
Health and safety		Marmoleum is REACH compliant to assure human safety and health.
	Renewable electricity	Marmoleum is manufactured using 100% electricity from renewable sources.
GBCA Green Star rating system		Marmoleum sheet is certified with GECA, LBC Red List Free and third-party verified EPD that can contribute to a project's Green Star rating through the Responsible Products credits, LEED, BREEAM and WELL.
	Application for underfloor heating	yes
Marmoleum meets the requirements of EN 14041:2004		
	DoP	0100201-DoP-107
	Reaction to fire	ISO 9239.1 Critical Radiant Flux Smoke Development Rate >4.5kW/m ² <750%.min
	Slip resistance	AS 4586 Appendix D & A R10, P3 ⁴
	Body voltage	EN 1815 Antistatic ≤ 2.0 kV
	Thermal conductivity	EN 12524 0.17 W/mK



¹ Marmoleum soul is a natural flooring material containing minimal to no added pigments. As a result, variations in colour shade and structure between production batches may be more pronounced than in other Marmoleum products. In addition, exposure to light may cause colour changes over time, similar to those observed in natural materials such as wood.
² Marmoleum sheet can be installed net fit, or with a welding rod in the seam. Both are proven hygienic solutions.
³ For details, please consult the Marmoleum soul EPD.
⁴ Slip test result achieved in an independent laboratory on a new sample. On-site testing is variable and may not guarantee the same result. For sustainable slip resistance, a particle-based floor must be used.



All Forbo Flooring Systems' manufacturing operations worldwide have a certified Quality Management System in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPDs) which can be found on all of our websites. Marmoleum is manufactured at an SA8000[®] -certified organisation.

Australia
 Forbo Flooring Systems
 23 Ormsby Place
 Wetherill Park, NSW 2164
 Tel: 1800 224 471
 Fax: 1800 662 566
 E-mail: info.au@forbo.com
 www.forbo-flooring.com.au

New Zealand
 Inzide Commercial
 Level 2, 34 Barrys Point Road
 Takapuna, Auckland 0622
 Tel: +64 9 441 9850
 Fax: +64 9 441 9851
 E-mail: sales@inzide.co.nz
 www.inzide.co.nz

Find us on



creating better environments



FLOORING SYSTEMS