

Page 1/9

Revision: 01.08.2024

Safety data sheet according to UK REACH

Printing date 01.08.2024

Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: 680 Elastilight
- · Article number: 680
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / preparation Tile adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271620

E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

· 1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Carc. 1B H350 May cause cancer.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated heavy naphthenic

· Hazard statements

H350 May cause cancer.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 2)

Printing date 01.08.2024 Version number 5 (replaces version 4) Revision: 01.08.2024

Trade name: 680 Elastilight

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Tile adhesive based on styrene acrylate and fillers

nents:	
1,2-benzisothiazol-3(2H)-one	>0.005-<0.05%
Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	>0.00015-<0.0015%
♠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ♠ Skin Corr. 1C, H314; Eye Dam. 1, H318;	
♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410	
Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 %	
Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
Eye Dam. 1; H318: C ≥ 0.6 % Eve Irrit 2: H319: 0.06 % < C <	
0.6 %	
Skin Sens. 1A; H317: C ≥ 0.0015 %	
	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 % mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Not applicable.
- After skin contact: Wash with water and soap.
- · After eve contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a physician.
- After swallowing: Rinse mouth with water and then drink plenty of water, consult physician immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 01.08.2024 Version number 5 (replaces version 4)

Trade name: 680 Elastilight

(Contd. of page 2)

Revision: 01.08.2024

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Collect product in waste container. Rinse floor with water.

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool, but frost-proof location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Recommended storage temperature between 15 and 25°C.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs			
2634-33-5	1,2-benzisothiazol-3(2H)-one		
Dermal	DNEL long term	0.966 mg/kg KG/d (wrk)	
	DNEL short term systemic health problems	0.345 mg/kg/d (Consumer)	
Inhalative	DNEL Inhalative long terme	1.2 /mg/m³ (Consumer)	

(Contd. on page 4)

Revision: 01.08.2024

Safety data sheet according to UK REACH

Printing date 01.08.2024 Version number 5 (replaces version 4)

Trade name: 680 Elastilight

		(Contd. of page 3	
	DNEL	6.81 mg/m³ (wrk)	
55965-84-	9 mixture of: 5-chloro-2-methyl- 2H-isothiazol-3-one [EC no. 220	4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl- 0-239-6] (3:1)	
Oral	DNEL	0.09 mg/kg (Consumer)	
Inhalative	DNEL Inhalative long terme	0.02 /mg/m³ (Consumer)	
·PNECs			
2634-33-5	1,2-benzisothiazol-3(2H)-one		
PNEC 4.99 μg/kg (Sea Water Sediment)		nt)	
	49.9 μg/kg (Fresh Water Sedim	49.9 μg/kg (Fresh Water Sediment)	
PNEC ug/l	0.403 μg/l (Sea Water)		
	4.03 μg/l (Fresh Water)		
PNEC mg/	/kg 3 mg/kg (Soil)		
55965-84-	9 mixture of: 5-chloro-2-methyl- 2H-isothiazol-3-one [EC no. 220	4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl- 0-239-6] (3:1)	
PNEC mg/	/kg 0.01 mg/kg (Soil)		
	0.027 mg/kg (Sea Water Sedim	nent)	
	0.027 mg/kg (Fresh Water Sed	iment)	

- · Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Not required.
- Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

· Material of gloves

Suitable chemical-resistant gloves (EN 374) even with longer direct contact (recommendation: protection index 6, corresponding> 480 minutes permeation time (permeation) according to EN 374) e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and others. Due to several factors that can influence (e.g. temperature), it must be taken into account that the service life of a chemical glove can in practice be considerably shorter than the permeation time indicated by the test.

The selection of suitable gloves does not only depend on the material, but also on further aspects of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material > 480 Minutes.
- For prolonged contact gloves made of the following materials are suitable: Chloroprene and butylrubber.

Nitrile rubber

(Contd. on page 5)

Printing date 01.08.2024 Version number 5 (replaces version 4) Revision: 01.08.2024

Trade name: 680 Elastilight

· Eye/face protection Goggles recommended during refilling

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:FluidLight grey

Odour: Weak, characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 100 °C

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.

· pH at 20 °C 8.5

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Not determined.
 Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C:
Relative density
Vapour density
Particle characteristics

1.15 g/cm³
Not determined.
Not determined.
Not applicable.

· 9.2 Other information

· Appearance:

Form: Paste

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· VOC(EC%) 0.00 %

· Change in condition

Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void
Flammable liquids Void
Flammable solids Void

(Contd. on page 6)

Printing date 01.08.2024 Version number 5 (replaces version 4) Revision: 01.08.2024

Trade name: 680 Elastilight

		(Contd. of page 5
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	vant for classification:	
2634-33-5	2634-33-5 1,2-benzisothiazol-3(2H)-one		
Oral	ATE	532 mg/kg ()	
Inhalative	ATE 4Hrs	0.4 mg/l (dust and mists)	
55965-84-	55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
Oral	LD50	64-66 mg/kg (rat)	
Dermal	LD50	87.12 mg/kg (rat)	

Skin corrosion/irritation

Possible irritation with prolonged or frequent contact.

Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity May cause cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 01.08.2024 Version number 5 (replaces version 4) Revision: 01.08.2024

Trade name: 680 Elastilight

(Contd. of page 6)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/3h 13 mg/ (Not specified)

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50/96h | 0.28 mg/l (LM)

0.188 mg/l (OM)

EC50/48 h | 0.126 mg/l (DM)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- Additional ecological information:
- General notes:

Do not discharge rinse water arising from cleaning tools into sewers or surface water.

Avoid transfer into the environment.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, ADN, IMDG, IATA Void
- · 14.2 UN proper shipping name
- · ADR, ADN, IMDG, IATA Void
- · 14.3 Transport hazard class(es)
- · ADR, ADN, IMDG, IATA
- Class

(Contd. on page 8)

Printing date 01.08.2024 Version number 5 (replaces version 4) Revision: 01.08.2024

Trade name: 680 Elastilight

		(Contd. of page 7
· 14.4 Packing group		
ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

7631-99-4 sodium nitrate, containing in the dry statemore than 16,3 per cent by weight of Listed nitrogen

· Reportable poisons

1310-73-2 sodium hydroxide

12% of total caustic alkalinity

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Printing date 01.08.2024

Version number 5 (replaces version 4)

Trade name: 680 Elastilight

(Contd. of page 8)

Revision: 01.08.2024

· Relevant phrases Toxic if swallowed. H301 H302 Harmful if swallowed. H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing SDS: R&D department

· Contact: Ing. T.W. Breeuwer

Version number of previous version: 4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity — Category 3
Acute Tox. 4: Acute toxicity — Category 4
Acute Tox. 2: Acute toxicity — Category 2
Skin Corr. 1C: Skin corrosion/irritation — Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 1B: Carcinogenicity - Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.