


eurocol

802

the strong connection

30-5-2026



EUROSTRIP BASIC

Self-adhesive edge strips made of PE foam. To prevent horizontal noise pollution. Also applicable for absorbing settlement when leveling, for example, floating screed floors or on wooden panels. Also prevents damage or contamination of the wall or skirting board when leveling or sanding the floor

PRODUCT TYPING

Base	PE-foam.
Color	White.
Roll length	25 m.
Format	Length 25 m. Width 20 mm. Thickness 5 mm.

- Easy application
- Self-adhesive
- Permanent elastic
- Don't rot
- Moisture-resistant
- Vapour permeable

PROPERTIES

Frost resistance	yes.
Special quality	self adhesive.

APPLICATION

802 Eurostrip Basic is suitable for any type of subfloor that is compressive and tensile resistant. The subfloor must also be flat, clean, permanently dry, free of grease and dirt, in accordance with the requirements stated in DIN 18 365. To prevent horizontal noise nuisance in combination with 820 DIM Floor. To prevent deformation during drying of the levelling compound due to expansion. As a barrier to compartmentalise when levelling a.s..

PROCESSING

Storage	Cool and dry, well sealed at normal temperature (5° - 30°C).
Tools	Knife or scissors.
Shelf Life	Minimum 36 Months, in unopened packaging.
Remarks	For the installation of higher layers of levelling compounds or 971 Europlan DE Rapid thin screed, we recommend the 806 Eurostripe Profile.

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

802 EUROSTRIP BASIC

Substrate:

- 802 Eurostrip Basic is suitable for any type of subfloor that is compressive and tensile resistant. The subfloor must also be flat, clean, permanently dry, free of grease and dirt, in accordance with the requirements as stated in DIN 18 365.
- Prime sanding subfloors with 044 Europrimer Multi, 049 Europrimer ABS or 099 Dispersion Primer.
- When leveling thicker layers, we recommend using the 806 Eurostrip Profile.
- Always consult our technical product information sheets in advance. If you have any doubts about the applications to be made, please contact our Technical Advice department in advance.

Instruction manual:

Remove the applied protective film from the self-adhesive side and place the 802 Eurostrip Basic tape directly on the desired location on the wall or floor. Then cut or trim the tape to the correct size.

Processing conditions:

Required subfloor temperature : min. 15 °C.
Temperature for material and surrounding : min. 18 °C.
Relative humidity : 35 - 75%.

ENVIRONMENT AND HEALTH

Hazard Class	None.
Safety and environment	Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste.

ITEM DATA

Article	Definition	Packaging	EAN-code
802	Eurostrip Basic	Carton of 1 roll of 25 m ¹ .	8 710345 802017



Package
25m

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturer's liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturer's influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG173114, Version 03, Stand 2018-11-20, ersetzt Ausgabe vom 2008-07-03.

802 EUROSTRIP BASIC

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | info.eurocol@forbo.com
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | info.eurocol.de@forbo.com

Eurocol is part of the Forbo Group

