

DoP (declaration of performance)

Declaration of performance

Nr. 965.1.1

965 EUROPLAN FLEX

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Self-levelling, superior levelling mortar for stony sub-floors for indoor use.	
3. Application	For producing even and absorbent substrates for flooring and parquet work.	
4. Name and contact address manufacturer	Forbo Eurocol Nederland B.V. Industrieweg 1-2 NL-1521 NA Wormerveer The Netherlands Tel. +31 75 6271600 Email: info.eurocol@forbo.com	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	FMPA Leipzig GmbH Hans-Weigel-Strasse 2b D 04319 Leipzig - Germany	
8. European Technical Assessment	n/a	
9. Declared performance	CA-C25-F6 according to DIN EN13813: 2003-01 Alpha hemihydrate - based coating compound for interior floor surfaces	
Essential characteristics	Performance	Test method
Tensile strength after 28 days	F6	NEN-EN 13892-2:2002
Compressive strength after 28 days	C25	NEN-EN 13892-2:2002
Material behaviour in case of fire	A1fl	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 2023-06-27 signed: ing. T.W. Breeuwer; Manager R&D 