

# eurocol 099

the strong connection



## DISPERSION PRIMER

Ready-to-use, highly impregnating primer for even better adhesion of sealants, tile adhesives and levelling compounds. The ideal bonding base on absorbent gypsum and cement-based walls and floors (indoors and outdoors), sheet material, etc. Thanks to GEV EMICODE EC 1PLUS (very low emission) also suitable for BREEAM projects.

### PRODUCT TYPING

|       |                     |
|-------|---------------------|
| Base  | Acrylic dispersion. |
| Color | Light pink.         |

- Very low emission
- EMICODE EC 1PLUS
- Non-flammable
- User friendly
- Favourable spreading capacity
- Multi-purpose application
- High penetration capacity
- For in- and outdoor use

### PROPERTIES

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| Aging              | 099 Dispersion Primer does not deteriorate with age.                        |
| Alkali resistance  | 099 Dispersion Primer is resistant against alkaline moisture.               |
| Classification     | Emicode EC 1PLUS tested conform EN 13999-2/4. Suitable for BREEAM-projects. |
| Consumption        | 6 - 9 m <sup>2</sup> per kg.                                                |
| Sensitive to frost | No.                                                                         |
| Specific weight    | 1.0 kg/l.                                                                   |

### APPLICATION

Primer for:

- improving the adhesion of sealants, tile adhesives and levelling compounds on absorbent gypsum or cement-based walls and floors, sheet material etc. Not suitable for impervious subfloors. Use 051 Europrimer Quartz.
- improving the top layer of cement screeds that tend to crumble on the surface.

### PROCESSING

|         |                                                           |
|---------|-----------------------------------------------------------|
| Storage | Store free from frost. Protect against high temperatures. |
|---------|-----------------------------------------------------------|

**099 DISPERSIEPRIMER**

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| <b>Tools</b>                   | Lambswool roller, brush or spray-gun.                                      |
| <b>Drying</b>                  | 1 - 2 hours, depending on temperature, relative humidity and subfloor.     |
| <b>Shelf Life</b>              | 12 Months, in unopened packaging. After use close the open packaging well. |
| <b>Application temperature</b> | From 5° to 25 °C (surrounding and subfloor temperature).                   |

*\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

#### Substrate:

- The subfloor should be clean, free from grease and dirt, dry and have a good tensile and compression strength, according to the requirements of DIN 18 353 and DIN 18 365.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

#### Instruction manual:

- Apply 099 Dispersion Primer thinly and evenly with a brush and/or lambswool roller.
- 099 Dispersion Primer can also be sprayed.
- Drying time 1 - 2 hours.
- Sandpaper old adhesive residues carefully and make dust-free.
- When installing tiles with 725 Alphycol on anhydrite floors keep a drying time of approx. 1 hour.
- Spreading capacity 100 - 150 g/m<sup>2</sup>.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

## QUALITY AND GUARANTEE



## ENVIRONMENT AND HEALTH

Safety and environment Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.

MSDS For extensive information about safety and environment we refer to our website [www.eurocol.nl](http://www.eurocol.nl).

## ITEM DATA

| Article | Definition        | Packaging                 | EAN-code        |
|---------|-------------------|---------------------------|-----------------|
| 099     | Dispersion Primer | 10 kg jerry can           | 8 710345 056502 |
| 099     | Dispersion Primer | Box of 12 bottles of 1 kg | 8 710345 099035 |
| 099     | Dispersion Primer | 1 kg bottle               | 8 710345 056519 |

### 099 DISPERSIEPRIMER