

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: 609 Eurostar Tex

· Article number: 609

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / preparation Flooring adhesive

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271600 - Fax +31 75 6283564 E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

· 1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains 1,2-benzisothiazol-3(2H)-one, mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Flooring adhesive based on acrylate copolymer, fillers and resin dispersed in water.

(Contd. on page 2)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

	(Contd. of	f page
Dangerous compor	nents:	
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	<19
EINECS: 220-120-9	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ♠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ♠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: $C \ge 0.6$ % Skin Irrit. 2; H315: 0.06 % ≤ $C < 0.6$ % Eye Dam. 1; H318: $C \ge 0.6$ % Skin Sens. 1A; H317: $C \ge 0.0015$ %	<19

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- After inhalation: Not applicable.
- After skin contact: Wash with water and soap.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a physician.

- After swallowing: Rinse mouth with water and consult physician immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Collect product in waste container. Rinse floor with water.

• **6.4 Reference to other sections** *No dangerous substances are released.*

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool, but frost-proof location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Recommended storage temperature between 15 and 25 ℃.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs			
2634-33-5	1,2-benzisothiazol-3(2H)-one		
Dermal	DNEL long term	0.966 mg/kg KG/d (wrk)	
	DNEL short term systemic health problems	0.345 mg/kg/d (Consumer)	
	DNEL Inhalative long terme	1.2 /mg/m³ (Consumer)	
	DNEL	6.81 mg/m³ (wrk)	
55965-84-	9 mixture of: 5-chloro-2-methyl-4-isothia isothiazol-3-one [EC no. 220-239-6] (3:1	azolin-3-one [EC no. 247-500-7] and 2-methyl-2F)	
Oral	DNEL	0.09 mg/kg (Consumer)	
Inhalative	DNEL Inhalative long terme	0.02 /mg/m³ (Consumer)	
PNECs			
2634-33-5	1,2-benzisothiazol-3(2H)-one		
PNEC	4.99 μg/kg (Sea Water Sediment)		
	49.9 μg/kg (Fresh Water Sediment)		
PNEC ug/l	0.403 μg/l (Sea Water)		
	4.03 μg/l (Fresh Water)		
PNEC mg/	/kg 3 mg/kg (Soil)	(Soil)	
55965-84-	9 mixture of: 5-chloro-2-methyl-4-isothia isothiazol-3-one [EC no. 220-239-6] (3:1	azolin-3-one [EC no. 247-500-7] and 2-methyl-2h)	
PNEC mg/	/kg 0.01 mg/kg (Soil)		

(Contd. on page 4)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 3)

0.027 mg/kg (Sea Water Sediment)
0.027 mg/kg (Fresh Water Sediment)

- · Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

Material of gloves

Suitable chemical-resistant gloves (EN 374) even with longer direct contact (recommendation: protection index 6, corresponding> 480 minutes permeation time (permeation) according to EN 374) e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and others. Due to several factors that can influence (e.g. temperature), it must be taken into account that the service life of a chemical glove can in practice be considerably shorter than the permeation time indicated by the test.

- · Penetration time of glove material > 480 Minutes.
- · For prolonged contact gloves made of the following materials are suitable:

Chloroprene and butylrubber.

Nitrile rubber

· Eye/face protection Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: Beige

· Odour: Characteristic • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 100 $^{\circ}$ C

· Flash point: Not applicable.

. pH at 20 ℃ 7.5

· Solubility

• water: Fully miscible. • Vapour pressure at 20 ℃: 23 hPa

Density and/or relative density

· Density at 20 °C: 1.5 g/cm³

- · 9.2 Other information
- · Appearance:

· Form: Paste

(Contd. on page 5)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 4)

Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

· Organic solvents: 0.0 %

·Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

Self-heating substances and mixtures
 Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

Desensitised explosives

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

Void

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral LD50 64-66 mg/kg (rat)
Dermal LD50 87.12 mg/kg (rat)

(Contd. on page 6)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 5)

- · Skin corrosion/irritation Possible irritation with prolonged or frequent contact.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

· 12.1 TOXIC	пу
· Aquatic to	xicity:
<i>2634-33-5</i>	1,2-benzisothiazol-3(2H)-one
EC50/3h	13 mg/l (Not specified)
<i>55965-84-</i> 9	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
LC50/96h	0.28 mg/l (LM)
	0.188 mg/l (OM)
EC50/48 h	0.126 mg/l (DM)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Do not allow large quantities to reach sewage system or surface water.

According to the criteria of the EU-classification and labelling "dangerous for environment" (93/21/EWG) the substance/ the product has to be classified as non-hazardous for the environment.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 6)

· Recommended cleansing agents: Warm water, if necessary together with cleansing agents.

SECTION 14: Transport information	on
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR · ADN, IMDG, IATA	Void Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according instruments	y to IMO Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

(Contd. on page 8)

Printing date 28.11.2022 Version number 3 Revision: 28.11.2022

Trade name: 609 Eurostar Tex

(Contd. of page 7)

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Contact: Ing. T.W. Breeuwer

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

GB