

1. Unique identification code of the product-type:

0200101-DoP-GB306

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Surestep, Safestep (EN 13845)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see BS EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Forbo Flooring UK Ltd., High Holborn Road, Ripley, Derbyshire, DE5 3NT, United Kingdom

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of notified certification body that performed the initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance.





TÜV Rheinland Nederland B.V.
Westervoortsedijk 73
6827 AV Arnhem, Netherlands

Notified laboratory n°336

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire		BS EN 14041: 2004/AC:2006
Content of Pentachlorophenol		
Formaldehyd Emissions		
Slip resistance		
Electrical behavior (dissipative)	NPD	
Electrical behavior (conductive)	NPD	
Electrical behavior (antistatic)	NPD	
Thermal conductivity [W/mK]	0.25 W/m.K	
Water-tightness	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Statutory Instrument 2019/465 and 2020/1359, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Director UK, Angus Fotheringhame

Ripley, 28-02-2024

