

FORBO MARMOLEUM SECOND LIFE TECHNICAL DATA

1. PRODUCT NAME & MANUFACTURER

1.1 Product:

Forbo Marmoleum Second Life restorative finish

1.2 Manufacturer:

Forbo Flooring Systems US
8 Maplewood Drive
Hazleton, PA 18202
1-800-842-7839

Forbo Flooring Systems Canada
3983 Nashua Drive, Unit 1
Mississauga, ON L4V 1P3
1-800-268-8108 (English)
1-800-567-9268 (French)

www.forboflooringNA.com

1.3 Product Description:

Marmoleum Second Life is a unique two-part field applied coating that can restore the surface of old, worn or improperly maintained Marmoleum. This two-coat system eliminates the routine of repeated stripping and coating the floor.

Marmoleum Second Life provides all the benefits of Topshield – Forbo's factory finish for Marmoleum. It is low odor for sensitive indoor environments and contains 0 VOC's – making this product safe for both building occupants and the environment.

Marmoleum Second Life is designed for use only with Forbo Marmoleum products.

1.4 Physical Characteristics:

Odor ----- Organic
Color ----- White
VOC Content ----- 1.69575%
Spread Rate ----- 650 sq ft for 2 coats per gallon
Unit Size ----- 1 gallon (3.785 L)
Shelf Life ----- 1 year in unopened container
Storage ----- Do NOT Freeze
Disposal ----- Follow all local regulations

2. EVALUATION, PREPARATION & APPLICATION

2.1 Evaluation & Preparation:

Contact Forbo's Product Support & Education Services team for assistance in assessing the condition of the floor for recommendations on repairs and the suitability to use Marmoleum Second Life for restoration of the floor.

Preparation of the floor may vary depending on the condition of the floor. All repairs and installation related issues should be addressed prior to applying Marmoleum Second Life. Small gouges and damage may be repaired with Forbo Marmoweld ETU. Always refer to and follow the recommendations in Forbo's General Floor Care Guidelines prior to starting any cleaning processes.

2.2 Mixing Guidelines:

Marmoleum Second Life is a two-part finish. Add entire contents of Part B to Part A. DO NOT mix partial units, following the mixing instructions.

IMPORTANT! Always wear proper PPE (Personal Protective Equipment) when working with Marmoleum Second Life. This includes gloves, clothing, eye and face protection.

2.3 Required Training:

Forbo requires those applying the Marmoleum Second Life attend a free virtual training prior to the use and application of Marmoleum Second Life. Contact Forbo's Product Support & Education Services team to schedule a training. Upon completion of the virtual training, full written guidelines will be provided to ensure all proper steps are followed.

Any claims for improper use or application of Marmoleum Second Life where no virtual training has been completed will be refused.

2.4 Application Guidelines:

Apply Forbo Marmoleum Second Life in a medium coat using a microfiber floor finish pad. Once the surface is dry to the touch, allow a minimum of 20 minutes before applying the second coat, and wait a minimum of 60 minutes for the floor to completely dry before allowing traffic.

Do not apply any other finishes on top of Marmoleum Second Life.

3. WARRANTY

Limited 5-year no reapplication warranty. For complete details, contact Forbo Flooring.

4. CARE & CLEANING

See Forbo's Marmoleum Floor Care Guidelines for full recommendations following the application of Marmoleum Second Life.