


DoP (declaration of performance)
Declaration of performance
Nr. 733.1.1

733 SUPERIOR S2

| | | |
|---|---|---|
| 1. Unique identification | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this adhesive. | |
| 2. Designation | | |
| 3. Application | | |
| 4. Name and contact address manufacturer | Forbo Eurocol Nederland B.V. Industrieweg 1-2 NL-1521 NA Wormerveer The Netherlands Tel. +31 75 6271600 Email: info.eurocol@forbo.com | |
| 5. Name and contact address authorized | n/a | |
| 6. System of assessment and verification of constancy of performance | 3 | |
| 7. Activity of the notified certification body as required by the harmonized standard | | |
| 8. European Technical Assessment | n/a | |
| 9. Declared performance | | |
| Essential characteristics | Performance | Test method |
| Initial adhesive strength | > 1 N/mm ² | NEN-EN 1348:2008 §8.2 |
| Adhesive strength after water exposure | > 1 N/mm ² | NEN-EN 1348:2008 §8.3 |
| Heat exposure | > 1 N/mm ² | NEN-EN 1348:2008 §8.4 |
| Adhesive strength after water exposure and freeze/thaw | > 1 N/mm ² | NEN-EN 1348:2008 §8.5 |
| Open time 20 minutes | > 1 N/mm ² | NEN-EN 1346:2008 |
| Material behaviour in case of fire | Class E | NEN-EN 13501-1:2007+A1:2009 |
| Released dangerous substances | see MSDS | |
| Optional characteristics | Performance | Test method |
| Extended open time 30 minutes | ≥ 0.5 N/mm ² | NEN-EN 1346:2008 |
| Flexibility | S2 (> 5 mm) | NEN-EN 12002:2008 |
| Declaration drafted in accordance with Annex ZA of NEN-EN 12004:2007+A1:2012. | | |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. | | |
| | | Wormerveer, 25-07-2019 signed: ing. T.W. Breeuwer; Manager R&D  |