

# eurocol

# 063

the strong connection



## EUROTAPE

Reinforcing tape for sealing horizontal and vertical tile connections in "wet areas", such as shower cubicles, bathrooms, utility rooms, etc. Also suitable for sealing connections of sheet material under tiling. To be used in combination with 685 Eurocoat or 683 Fibrecoat

### PRODUCT TYPING

|       |                                                    |
|-------|----------------------------------------------------|
| Base  | Fabric made of polyester and polypropylene fibres. |
| Color | White.                                             |

- Flexible
- Elastic
- Seam sealing

### PROPERTIES

|                     |                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------|
| Alkali resistance   | Resistant against alkaline moisture.                                                                         |
| Elasticity          | In combination with 685 Eurocoat sufficiently elastic to intercept movement in the construction in practice. |
| Sensitive to frost  | No.                                                                                                          |
| Humidity resistance | Insensitive to moisture.                                                                                     |

### APPLICATION

For sealing horizontal and vertical corner connections of tile work in "wet areas", e.g. shower cabins, bathrooms, professional kitchens etc. Also suitable for sealing connections between board materials under tile work. Use in combination with 685 Eurocoat or 683 Fibrecoat.

### PROCESSING

|                     |                          |
|---------------------|--------------------------|
| Storage             | Store dry.               |
| Moisture resistance | Insensitive to moisture. |
| Shelf Life          | Unlimited.               |

*\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

#### Substrate:

- 063 Eurotape can be applied on almost any type of subfloor that is clean and free from grease and dirt.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

#### Instruction manual:

See directions for use of 685 Eurocoat.

**063 EUROBAND**

---

## ENVIRONMENT AND HEALTH

---

MSDS For extensive information about safety and environment we refer to our website [www.eurocol.nl](http://www.eurocol.nl).

---

## ITEM DATA

---

| Article | Definition        | Packaging                                                                    | EAN-code        |
|---------|-------------------|------------------------------------------------------------------------------|-----------------|
| 063     | Eurotape          | Box of 100 m <sup>1</sup>                                                    | 8 710345 057301 |
| 063     | Eurotape          | Box of 4x25 m <sup>1</sup>                                                   | 8 710345 001038 |
| 685/063 | Eurocoat/Eurotape | Do-it-yourself packaging of 4 kg 685 Eurocoat/12 m <sup>1</sup> 063 Eurotape | 8 710345 003612 |

BG172063, Version 01, Stand 2022-08-30,

### 063 EUROBAND

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | [info.eurocol@forbo.com](mailto:info.eurocol@forbo.com)  
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | [info.eurocol.de@forbo.com](mailto:info.eurocol.de@forbo.com)

Eurocol is part of the Forbo Group

