

creating better environments

Rodbo FLOORING SYSTEMS Using cut and loop design technology, the tip-sheared aesthetic of Perspective delivers a feeling of luxury that is perfect for modern workspaces.

The blend of surface textures within each tile absorbs light differently, creating a rich and opulent all-over visual which subtly changes from differing perspectives within any interior.

- 8 neutral tones complemented by 6 rich, decadent accent colours, each colour tone combines two yarn colours, creating a modern, softly striated design
- 100% solution-dyed, Refresh® by Universal Fibers®. Nylon 66 and Nylon 6 with 30% recycled content
- Monolithic installation with seamless broadloom appearance
- Easily combined with Allura Flex vinyl LVT using the same tackifier, and Allura Ease adhesive free vinyl LVT, without the need for transition strips, additional profiles, or inconvenient build-up of the sub-floor
- Meets Ska criteria for M12 soft floor coverings
- Contains 65% recycled content by weight
- Designed, manufactured and stocked in the UK



65% recycled content by weight



tip sheared loop construction for structure and pattern



50cm x 50cm carpet tile

Cover image:

3907 | melodious + **3905** | ethereal + **3908** | vivacious




































Perspective colour options



Perspective installation ideas



Perspective fitting options



Forbo Environmental Data Sheet

Product name	Tessera Perspective
Product description	Tessera Perspective is a tufted cut and loop pile carpet tile Nylon 66 and Nylon 6 pile composition, available in 14 colourways. Perspective complies with all requirements of EN 1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000°



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content	CEO(ISO 9001 Quality Management System	CERNIED OSOI
of product by weight	65%	ISO 14001 Environmental Management System	ISO 14001
Post industrial recycled content	65%	ISO 45001 Occupational Health and Safety Management	ISO 45001 Occupational Penalth and Safety Measagement CERTIFIED
% renewable electricity & biogas used	100%	Perspective is made in an SA8000° certified facility	SAI
Carbon footprint			
Estimated carbon footprint using	Raw materials and production	Awaiting result of the EPD	
data from Environmental product declaration according to ISO 14025	Use (1 year)	Awaiting result of the EPD	

Your footsteps - how it performs

Impact sound reduction 25 c	dЕ
-----------------------------	----

Installation

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended.

Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.

Forbo Environmental Data Sheet – continued

Maintenance				
	Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems.			
	All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less than the normal system of cleaning, produces no waste product, uses non hazardous and biodegrada cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.			
End of life				
		cycling, downcycling and waste to energy. Forbo Flooring Systems works lean, reuse and recycle old carpet tiles in the UK.		
Contribution to Green	Building Schemes			
BREEAM 2018				
	Awaiting the result of the EPD			
LEED (version 4)				
Potential direct or indirect contribution to following categories and credits:	Materials and Resources			
		Construction and demolition waste management up to 2 points		
	Indoor environmental quality	Low emitting materials up to 3 points		
		Acoustic performance up to 1 point		
Forbo design principles (Redu	ce, Recycle, Reuse, Renew)			
Reduce	Investment in an extruder has reduced our bitumen usage by 50%.			
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.			
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles made in the UK contain at least 56% recycled content by weight.			
	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).			

Technical specification

Tessera Perspective carpet tiles meet the requirements of EN 1307

	Description		Tufted cut and loop pile carpet tile
	Dimensions	EN 994	50cm x 50cm
	Total thickness	ISO 1765	6.1mm
	Pile height	ISO 1766	3.0mm
	Collection size		14 colourways. 4m² per box
 - 	Commercial use	EN ISO 10874	Class 33, Suitable for any type of heavy contract application
	Pile composition		100% Refresh® by Universal Fibers®. Nylon 66 and Nylon 6 with 30% recycled content
	Dye method		100% solution dyed
	Stitch density	ISO 1763	181,440 per m ²
3	Pile weight	ISO 8543	670 g/m²
	Total weight	ISO 8543	4185 g/m²
	Primary backing		Polyester
	Secondary backing		ProBac™ modified bitumen and polyester fleece. Contains over 76% recycled content.
	Alternative available secondary backing		SOFTbac [®]
	Acoustical impact noise reduction	ISO 717-2	25 dB
)	Acoustical sound absorption reduction	ISO 354	aw = 0.15 (H)
	Castor chair continuous use	ISO 4918	r ≥ 2.4 continuous use
\$	Colour fastness to light	EN ISO 105-B02	≥6
KN	Dimensional stability	EN 986	≤ 0.2%
	Creating Better Environments		
T C	Renewable Energy Recycled Content		All Tessera tufted carpet tiles are manufactured using 100% renewable energy (electricity & biogas) Perspective carpet tiles contain 65% recycled content by weight
£3	7.		
` ₹ ⊘∂	Indoor Air Quality		Perspective carpet tiles comply to 01350 Indoor Air Quality Standard
BACK TO THE FLOOR RECYCLING PROGRAM	Back to the Floor		Installation off cuts can be collected via Back to the Floor
\Box	Ska Rating		Perspective meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Installation method		Monolithic
	Perspective carpet tiles meet the requirements of EN 14041:2004		
CE	Product code	EN 14041:2004	1170100-DoP-101
G B ₁₋₈₁ NCS	Reaction to fire	EN 13501-1	B _{fl} -s1, G, NCS
1	Slip resistance	EN 13893	µ ≥ 0.30
<u> </u>	Body voltage	ISO 6356	< 2.0 kV
λ ₂₃ <i>ttt</i>	Thermal conductivity	EN 12524	0.06 W/mK

Contact us



Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring and movement systems, and offers a full range of flooring products for commercial and affordable housing and new build markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering total flooring solutions for any indoor environment.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this brochure are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this brochure and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.

UK

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Email: info.flooring.uk@forbo.com

London EC1 showroom

79 St John Street, Clerkenwell London EC1M 4NR Tel: 0207 553 9300 Email: ec1@forbo.com

For commercial enquiries:

If calling from the North, London & South East Tel: 0800 0282 162 bcs.flooring.uk@forbo.com

If calling from Scotland, Midlands & South West Tel: 0800 0935 258 kcs.flooring.uk@forbo.com

Nuway enquiries:

Tel: 01773 740 688 efs.flooring.uk@forbo.com

Residential enquiries:

Tel: 0800 0935 846 Email: krcs.flooring.uk@forbo.com www.forbo-flooring.co.uk

SAMPLE SERVICE 0800 731 2369

Samples can be ordered over the phone, by calling **0800 731 2369**

(Mon-Fri, 8.30am-5.00pm)

Samples can be ordered 24/7 by visiting www.forbo-flooring.co.uk/samples or by emailing samples.uk@forbo.com

Ireland

Forbo Ireland Ltd 2 Deansgrange Business Park Blackrock Co Dublin

Tel: 00353 1 2898 898 Fax: 00353 1 2898 177 Email: info.ireland@forbo.com www.forbo-flooring.ie

Registered office:

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Registered in England 9200318

