

Product quick info

**E 3/1 U2/U2 BT/SMT-HACCP-
PS white FDA**

Sketch of cross-section (not actual size)

Applications

- Dough conveying
- Meat, poultry and seafood processing
- Processing of dairy products
- Fruit and vegetable processing
- Mini conveyor

Properties/Advantages

- Both sides coated
- Hydrolysis resistant urethane coating with semi-matt top face pattern
- Broken twill (BT) pattern coated underside
- Pre-shrunk (PS) tension member
- Laterally stiff fabric
- HACCP design
- Complies to FDA, EU and MHLW# 370 regulation for direct contact to foodstuffs

Basic technical data

Top face	Polyurethane, SMT
Underside	Polyurethane, BT
Article no.	904496
d _{min} [mm]	20
Total thickness [mm]	1.5
k _{1%} relaxed [N/mm width]	2.5
Weight [kg/m ²]	1.6
Permitted operating temperature [°C]	-30 to +100

Product Quick Info | EN | 02.2024

FMS - Reproduction of text or parts thereof only with our approval. Modifications reserved.

Forbo Siegling GmbH
Lilienthalstrasse 6/8, D-30179 Hannover
Phone +49 511 67 04 0
www.forbo-siegling.com, siegling@forbo.com