

eurocol

099

the strong connection



DISPERSION PRIMER

Ready-to-use, highly impregnating primer for even better adhesion of sealants, tile adhesives and levelling compounds. The ideal bonding base on absorbent gypsum and cement-based walls and floors (indoors and outdoors), sheet material, etc. Thanks to GEV EMICODE EC 1PLUS (very low emissions) also suitable for BREEAM projects.

PRODUCT TYPING

Base	Acrylic dispersion.
Color	Light pink.

- Very low emission
- EMICODE EC 1PLUS
- Non-flammable
- User friendly
- Favourable spreading capacity
- Multi-purpose application
- High penetration capacity
- For in- and outdoor use

PROPERTIES

Aging	099 Dispersion Primer does not deteriorate with age.
Alkali resistance	099 Dispersion Primer is resistant against alkaline moisture.
Classification	Emicode EC 1PLUS tested conform EN 13999-2/4. Suitable for BREEAM-projects.
Consumption	6 - 9 m ² per kg.
Sensitive to frost	No.
Specific weight	1.0 kg/l.

APPLICATION

Primer for:

- improving the adhesion of sealants, tile adhesives and levelling compounds on absorbent gypsum or cement-based walls and floors, sheet material etc. Not suitable for impervious subfloors. Use 051 Europrimer Quartz.
- improving the top layer of cement screeds that tend to crumble on the surface.

PROCESSING

Storage	Store free from frost. Protect against high temperatures.
---------	---

099 DISPERSIEPRIMER

Tools	Lambswool roller, brush or spray-gun.
Drying	1 - 2 hours, depending on temperature, relative humidity and subfloor.
Shelf Life	12 Months, in unopened packaging. After use close the open packaging well.
Application temperature	From 5° to 25 °C (surrounding and subfloor temperature).

* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- The subfloor should be clean, free from grease and dirt, dry and have a good tensile and compression strength, according to the requirements of DIN 18 353 and DIN 18 365.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Instruction manual:

- Apply 099 Dispersion Primer thinly and evenly with a brush and/or lambswool roller.
- 099 Dispersion Primer can also be sprayed.
- Drying time 1 - 2 hours.
- Sandpaper old adhesive residues carefully and make dust-free.
- When installing tiles with 725 Alphycol on anhydrite floors keep a drying time of approx. 1 hour.
- Spreading capacity 100 - 150 g/m².

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

QUALITY AND GUARANTEE



ENVIRONMENT AND HEALTH

Safety and environment Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.

MSDS For extensive information about safety and environment we refer to our website www.eurocol.nl.

ITEM DATA

Article	Definition	Packaging	EAN-code
099	Dispersion Primer	10 kg jerry can	8 710345 056502
099	Dispersion Primer	Box of 12 bottles of 1 kg	8 710345 099035
099	Dispersion Primer	1 kg bottle	8 710345 056519

099 DISPERSIEPRIMER