

Technical specifications

	Total thickness	EN ISO 24346	2.0 mm
	Collection size		24
	Roll width	EN ISO 24341	1.83 m
	Roll length	EN ISO 24341	≤ 30 m
	Total weight	EN ISO 23997	2100 g/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
	Colour fastness to light	EN ISO 105-B02 method 3	≥ 6
	Gloss level	ISO 2813	< 5
	Flexibility	EN-ISO 24344	ø 50 mm
	Resistance to chemicals	EN ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
	Heat resistance		70 °C
	Antistatic	EN 1815	≤ 2.0 kV
	Creating better environments	LCA is the foundation for securing the lowest environmental impact Furniture Linoleum is climate positive cradle to gate*	
	Natural materials	Made with 94% natural ingredients (e.g. linseed oil, rosin, wood flour). Contains PEFC certified wood flour. Contains FSC certified paper.	
	Recycled content	Contains ingredients derived from recycled sources coming from post-industrial streams.	
	Health and safety	REACH compliant to assure human safety and health.	
	Renewable electricity	Manufactured using 100% electricity from renewable sources.	

* For details, please consult the Furniture Linoleum EPD.

Furniture Linoleum is a natural product, so there can be slight colour variations in different batches.

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites. Furniture Linoleum is manufactured at an SA8000® - certified organisation.

