eurocol

**DoP (declaration of performance)**
**Declaration of performance**
**Nr.** 975.1.3

# 975 EUROPLAN SPECIAL (Made in Holland)

| | | |
|---|---|---|
| 1. Unique identification | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar. | |
| 2. Designation | Forbo Eurocol Nederland 975 Europlan Special : a self-levelling project levelling mortar for stony sub-floors. | |
| 3. Application | For levelling cement-bound stony sub-floors and other stony sub-floors in layers of 2 to 10 mm thick that need to be covered with flooring. | |
| 4. Name and contact address manufacturer | *Forbo Eurocol Nederland B.V.*<br>*Industrieweg 1-2*<br>*NL-1521 NA Wormerveer The Netherlands*<br>*Tel. +31 75 6271600*<br>*Email: info.eurocol@forbo.com* | |
| 5. Name and contact address authorized | n/a | |
| 6. System of assessment and verification of constancy of performance | 4 | |
| 7. Activity of the notified certification body as required by the harmonized standard | n/a | |
| 8. European Technical Assessment | n/a | |
| 9. Declared performance | CT-C30-F7<br>in accordance with NEN-EN 13813:2002<br>Cement-bound self-levelling levelling mortar for use inside buildings. | |
| **Essential characteristics** | Performance | Test method |
| Tensile strength after 28 days | F7 | NEN-EN 13892-2:2002 |
| Compressive strength after 28 days | C30 | NEN-EN 13892-2:2002 |
| Material behaviour in case of fire | Class F | NEN-EN 13501-1:2007+A1:2009 |
| Released dangerous substances | see MSDS | |
| Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002 | | |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. | | |
| | Wormerveer, 24-05-2017<br>signed: ing. T.W. Breeuwer; Manager R&D | |

