

Technical specifications

allura click flexcore

Allura click Flexcore meets the requirements of EN-ISO 11638

| | | | |
|--|----------------------------------------------|-------------------------|----------------------------------------------------------------------|
| | Total thickness | EN-ISO 24346 | 6.3 mm |
| | Wear layer thickness | EN-ISO 24340 | 0.55 mm |
| | Collection size | | 20 |
| | Domestic use | EN-ISO 10874 | Class 23 |
| | Commercial use | EN-ISO 10874 | Class 33 |
| | Industrial use | EN-ISO 10874 | Class 42 |
| | Squareness and straightness | EN-ISO 24342 | < 400 mm < 0.25 mm / > 400mm < 0.35 mm |
| | Total weight | EN-ISO 23997 | 7900 g/m ² |
| | Wearlayer binder content | EN-ISO 11638 | Type 1 |
| | Castor chair continuous use | ISO 4918 | Pass |
| | Slip resistance (ramp test) | DIN 51130 | R10 |
| | Acoustical impact noise reduction | EN-ISO 717-2 | 20 dB |
| | Residual indentation <i>Typical value</i> | EN-ISO 24343-1 | ≤ 0.15 mm ~ 0.12 mm |
| | Colour fastness to light | EN-ISO 105-B02 method 3 | ≥ 6 |
| | Resistance to chemicals | EN-ISO 26987 | Very good |
| | Dimensional stability | EN-ISO 23999 | ≤ 0.05% |
| | Indoor Air Emissions: TVOC after 28 days | EN 16516 | ≤ 0.02 mg/m ³ |
| | Life Cycle Assessment | | LCA is the foundation for securing the lowest environmental impact |
| | Creating better environments | | |
| | Renewable electricity | | Allura is manufactured using 100% electricity from renewable sources |
| | Recycled content (mass) | | 30% |

Allura meets the requirements of EN 14041:2004 and BS EN 14041:2004

| | | | |
|--|----------------------|------------------|----------------------------|
| | Product code | EN 14041:2004 | 0200140-DoP-304 |
| | Product code | BS EN 14041:2004 | 0200101-DoP-GB304 |
| | Reaction to fire | EN 13501-1 | B _f -s1, L, NCS |
| | Slip resistance | EN 13893 | μ ≥ 0.30 |
| | Thermal conductivity | EN 12524 | 0.25 W/mK |
| | Body voltage | EN 1815 | ≤ 2.0 kV |

Recommended adhesives: For the latest installation instructions and recommended adhesives please visit www.forbo-flooring.co.uk/installation

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Allura is manufactured in a facility certified to SA8000 and OHSAS 18001.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.



For more information:

e: info.flooring.uk@forbo.com

t: **0800 0282 162**

w: forbo-flooring.co.uk/allura