

DoP (declaration of performance)
Declaration of performance
Nr. 925.1.2

925 EUROPLAN ALPHY DIRECT

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Forbo Eurocol Nederland 925 Europlan Alphy Direct; self-levelling, very high-grade, low-tension curing levelling mortar.	
3. Application	For direct levelling, in layers of 2 to 30mm, of anhydrite floors, old glue remains on all permanently dry, stony floors, poured concrete foundations, smooth and sealed sub-floors such as granito, terrazzo, etc. that need to be covered with flooring.	
4. Name and contact address manufacturer	<i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i>	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	n/a	
8. European Technical Assessment	n/a	
9. Declared performance	CA-C30-F10 in accordance with NEN-EN 13813:2002 Calcium sulphate-bound self-levelling levelling mortar for use inside buildings, where priming the sub-floor in advance is generally unnecessary.	
Essential characteristics	Performance	Test method
Tensile strength after 28 days	F10	NEN-EN 13892-2:2002
Compressive strength after 28 days	C30	NEN-EN 13892-2:2002
Material behaviour in case of fire	Class F	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 28-09-2015 signed: ing. T.W. Breeuwer; Manager R&D 