

# eurocol

# 043

the strong connection



## EUROPRIMER ALPHY

Primer specially designed for highly absorbant anydrite floors.

---

### PRODUCT TYPING

---

Base	Acrylic dispersion.
Color	Green.
Consistency	Thin liquid.

---

- Very low emission
  - Emission EC 1PLUS
  - High coverage efficiency
- 

### PROPERTIES

---

Classification	Emission EC 1PLUS tested conform EN 13999-2/4.
Consumption	100 – 200 g/m <sup>2</sup> , for absorbant floors.*
Flammability	Non-flammable.
Specific weight	Approx. 1.02 kg/l.

---

### 043 EUROPRIMER ALPHY

---

## APPLICATION

---

Primer for improving adhesion of plaster-bound levelling compounds to prevent elephant skin effects in the levelling layer, if the surface of an anhydrite floor is locally or globally highly absorbent.

---

## PROCESSING

---

Storage	Store cool and free from frost.
Tools	Lambswool roller.
Drying	1 - 2 hours.*
Shelf Life	12 months, in unopened packaging.
Cleaner	Water.

\* The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

### Substrate:

- The anhydrite floor must be stable to pressure and traction. The subfloor must also be level, clean, permanently dry, and free of grease, dirt and dust, as per the requirements outlined in DIN 18 365.
- Always consult our technical product data sheets if in doubt. If you have any doubts about using a product, contact our Technical Advice department.

### Instruction manual:

- Shake the packaging well before use.
- Apply 043 Europrimer Alphy evenly using a napped roller. Please ensure sufficient primer is applied by regularly loading the roller with fresh product.
- 043 Europrimer Alphy may also be sprayed if desired.
- Do not walk on the floor while the product is drying.
- Once the primer has dried, the floor can be finished further.
- Clean tools immediately with water.
- Remove fresh stains immediately with water.
- Avoid contact with eyes and skin and use suitable personal protection equipment (please refer to our safety sheet).
- Clean product traces and dispose of cleaning water according to locally applicable environmental regulation and do not dispose of in the sewer.

### Working conditions:

Required surrounding temperature : 18 - 23 °C.  
Temperature for material and subfloor : min. 15° – max. 20 °C.  
Relative humidity : 40 - 70%.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

---

## QUALITY AND GUARANTEE

---



---

## ENVIRONMENT AND HEALTH

---

Hazard Class	None.
MSDS	For detailed information about the safety measures please refer to the safety information sheet on our website <a href="http://www.eurocol.nl">www.eurocol.nl</a> .

---

## ITEM DATA

---

Article	Definition	Packaging	EAN-code
---------	------------	-----------	----------

**043 EUROPRIMER ALPHY**

043    Europrimer Alphy    10 kg jerry can    8 710345 043014

**043 EUROPRIMER ALPHY**

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | [info.eurocol@forbo.com](mailto:info.eurocol@forbo.com)  
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | [info.eurocol.de@forbo.com](mailto:info.eurocol.de@forbo.com)

Eurocol is part of the Forbo Group

