

Product quick info

UU 20U-11 FSTR/GL

black/white HACCP FDA



Sketch of cross-section (not actual size)

Applications

- X-ray detector
- Clean room applications
- Conveying of electronic goods
- Checkweigher
- Labelling machines
- Buffer conveyors, slicers

Properties/Advantages

- Smooth (GL) top face for increasing COF against packaged food products, to ensure "getting-thru heavy curtain" to X-ray detector
- Elastic belt design
 - for excellent tracking properties
 - short center distances are possible
 - avoiding of shadow formation in the splicing area
- Antistatic properties for ensuring no static charge by use of X-ray
- High level of resistance to grease and oil
- Compliance to food regulations: FDA 21CFR, MHLW 370, EU 10/2011 and EC 1935/2004

Basic technical data

Top face	Polyurthane, smooth
Friction coating	Polyurethane, fine texture
Article no.	855665
d _{min} [mm]	10
Total thickness [mm]	1.1
F _w value [N/mm width]	0,25
Weight [kg/m ²]	1.15
Permitted operating temperature [°C] -20 to +60	

Product Quick Info | EN | 10.2025

FMS · Reproduction of text or parts thereof only with our approval. Modifications reserved.

Forbo Siegling GmbH

Lilienthalstrasse 6/8, D-30179 Hannover

Phone +49 511 67 04 0

www.forbo-siegling.com, siegling@forbo.com

PQI

siegling extremultus

NEW