

Forbo Adhesive Fast Facts Chart

This chart is intended for use as a general guide only.

Refer to the Technical Data Sheets for the full details on each specific adhesive or contact Product Support & Education Services *PRIOR* to installation.

Forbo Adhesive	Adhesive Type	Packaging	Max Surface Moisture	Max MVE (per 1,000 ft ²)	Max RH	Max pH	Approximate Spread Rate (ft ² /gallon)	Adhesive Color	Trowel Notch	Freeze/Thaw Stability	Shelf Life (Unopened)
Sustain 1195	Dual Acrylic Polymer	1 Gallon 4 Gallon	n/a	10	90 - 95%	11	125	Green	1/16" x 1/16" x 1/16" square	1 Cycle at 20°F (-6° C)	2 Years
Sustain 100	Dual Acrylic Polymer	4 Gallon	< 5	n/a	100%	12	125	Blue	1/16" x 1/16" x 1/16" square	1 Cycle at 20°F (-6° C)	2 Years
MarmoSecure Tile Adhesive	Silane Modified Polymer	4 Gallon	n/a	n/a	100%	12	200	Black color that dries translucent black	1/32" x 1/16" x 1/32" U notch trowel	Do NOT Freeze	1 Year
FST 1299	High Quality Acrylic Emulsion	4 Gallon	< 5	n/a	99%	12	125	Yellow; Dries Clear	1/16" x 1/16" x 1/16" square OR 3/8" nap roller	1 Cycle at 20°F (-6° C)	2 Years
V 1190	Acrylic Polymer	1 Gallon 4 Gallon	n/a	8	90%	11	125 - 300	White	1/16" x 1/16" x 1/16" square OR 1/32" x 1/16" x 1/32" fine notch OR 3/8" nap roller	1 Cycle at 20°F (-6° C)	2 Years
C 930	Acrylic Polymer	1 Gallon 4 Gallon	n/a	8	85%	10	125	White with grey conductive fibers	1/16" x 1/16" x 1/16" square	1 Cycle at 20°F (-6° C)	2 Years
L 910W	Acrylic Polymer	1 Gallon 4 Gallon	n/a	n/a	n/a	n/a	90 - 125	Light Tan	1/8" x 1/8" x 1/16" V notch OR 1/16" x 1/16" x 1/16" square	1 Cycle at 20°F (-6° C)	2 Years
ArmorFix	Dual Acrylic Polymer	4 Gallon	n/a	n/a	n/a	12	128 - 146 Linear Feet	White	1/8" x 1/8" V-notch	1 Cycle at 20°F (-6° C)	2 Years
660	Two-Part Urethane	1.5 Gallon	n/a	6	80%	12	200 - 330	Beige	1/16" x 1/16" x 1/16" square OR 1/32" x 1/16" x 1/32" fine notch	Do NOT Freeze	1 Year