

|   |  |   |
|---|--|---|
| 1. Unique identification  | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this adhesive.   |   |
| 2. Designation  | Forbo Eurocol Nederland 777 Flexicol grey; flexible, white powdered tile adhesive.   |   |
| 3. Application  | Very flexible gluing ceramic wall and floor tiles, glass and ceramic mosaics and dark coloured natural stone to almost any surface. Suitable for interior application.   |   |
| 4. Name and contact address manufacturer  | <i>Forbo Eurocol Nederland B.V.</i><br><i>Industrieweg 1-2</i><br><i>NL-1521 NA Wormerveer The Netherlands</i><br><i>Tel. +31 75 6271600</i><br><i>Email: info.eurocol@forbo.com</i>   |   |
| 5. Name and contact address authorized  | n/a  |   |
| 6. System of assessment and verification of constancy of performance  | 3  |   |
| 7. Activity of the notified certification body as required by the harmonized standard   | The registered certifying body IKOB-BKB, identification no. 0957, performed the activities under system 3 and showed that the tile adhesive in question fulfils the initial type certification requirements described in Annex ZA of NEN-EN 12004:2007+A1:2012 and issued the certification of performance constancy and the conformity certificate. |   |
| 8. European Technical Assessment  | n/a  |   |
| 9. Declared performance   | C2TE in accordance with NEN-EN 12004:2007+A1:2012; an improved flexible, cement-bound powdered tile adhesive with increased strength and extended open time.   |   |
| <b>Essential characteristics</b>  | <b>Performance</b>   | <b>Test method</b>  |
| Initial adhesive strength   | ≥ 1 N/mm <sup>2</sup>  | NEN-EN 1348:2008 §8.2   |
| Adhesive strength after water exposure  | ≥ 1 N/mm <sup>2</sup>  | NEN-EN 1348:2008 §8.3   |
| Heat exposure   | ≥ 1 N/mm <sup>2</sup>  | NEN-EN 1348:2008 §8.4   |
| Adhesive strength after water exposure and freeze/thaw  | ≥ 1 N/mm <sup>2</sup>  | NEN-EN 1348:2008 §8.5   |
| Open time 20 minutes  | ≥ 1 N/mm <sup>2</sup>  | NEN-EN 1346:2008  |
| Material behaviour in case of fire  | Class E  | NEN-EN 13501-1:2007+A1:2009   |
| Released dangerous substances   | see MSDS   |   |
| <b>Optional characteristics</b>   | <b>Performance</b>   | <b>Test method</b>  |
| Increased sagging resistance  | ≤ 0.5 mm   | NEN-EN 1308:2008  |
| Extended open time 30 minutes   | ≥ 0.5 N/mm <sup>2</sup>  | NEN-EN 1346:2008  |
| Declaration drafted in accordance with Annex ZA of NEN-EN 12004:2007+A1:2012.   |  |   |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. |  |   |
|   |  | Wormerveer, 22-08-2013<br>signed: ing. T.W. Breeuwer; Manager R&D<br> |