

FORBO FLOORING ADHESIVE GUIDE

Product	Brand	Recommended adhesive		Packaging	Spread rate ¹	Applicator
Entrance textile matting	Coral sheet ranges - Brush, Classic, Duo	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Coral tile ranges - Brush, Classic, Interior	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
		FPS1	PS	15L	≥ 56m ² ≥ 105m ²	1.6mm V-Notch trowel minimum 10mm long nap roller
Linoleum	Marmoleum sheet - Marbled, Solid, Linear, Acoustic & Modular	611 Eurostar Lino Plus	HS	10L/11kg	28-35 m ²	2.4mm V-Notch trowel
	Marmoleum Decibel	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Marmoleum Ohmex	615 Eurostar Lino EC	EC	10L/11kg	≥ 42m ²	2.4mm V-Notch trowel
	Furniture Linoleum (Desktop)	611 Eurostar Lino Plus	HS	10L/11kg		Nap roller
	Bulletin Board	611 Eurostar Lino Plus	HS	10L/11kg		Nap roller
Luxury vinyl tiles	Allura Flex	F34	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
Vinyl sheet	Surestep, Safestep	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Onyx Harmony vinyl wall covering	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Eternal ranges - Eternal, Eternal de luxe, Original, DP	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Sarlon ranges - 15 dB, 19 dB, Compact	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Sphera ranges - Element, Energetic, Elite, Essence	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
Static control vinyl	Colorex SD/EC	641 Eurostar Special EC	EC	10L/12kg	≥ 42m ²	1.6mm V-Notch trowel
	Sphera SD/EC	641 Eurostar Special EC	EC	10L/12kg	≥ 42m ²	1.6mm V-Notch trowel
Flotex	Flotex sheet ranges - Colour, Borders, Vision, Designer	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Flotex tile & plank ranges	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
		FPS1	PS	15L	≥ 56m ² ≥ 105m ²	1.6mm V-Notch trowel minimum 10mm long nap roller
Carpet tiles	Tessera carpet tiles & plank ranges	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
		FPS1	PS	15L	≥ 56m ² ≥ 105m ²	1.6mm V-Notch trowel minimum 10mm long nap roller
Underlay	Sarlibase Acoustic underlay	F54	HS	12L/14kg	≥ 56m ²	1.6mm V-Notch trowel
	Corkment underlay	611 Eurostar Lino Plus ²	HS	10L/11kg	≥ 36m ²	2.4mm V-Notch trowel

¹ The open time of adhesives can be influenced by substrate porosity and environmental conditions. It is crucial to adhere to the manufacturer's instructions when applying adhesives, ensuring accurate spread rates and proper transfer. Failure to comply with these guidelines may impact warranty conditions.

² Corkment is fully adhered to the subfloor using 611 Eurostar Lino Plus, with Marmoleum using 611 ensure the jute hessian side is facing upwards (adhering hessian to hessian) with Flotex or Tessera, ensure the smooth cork is facing upwards using recommended adhesive.

The listed adhesives are available direct from Forbo Flooring.

For further technical information, visit www.forbo-flooring.com.au/installation, call 1800 224 471 or email technical.au@forbo.com.

HS Hard stick

PS Pressure sensitive

EC Electrically conductive