


| | | |
|---|---|---|
| 1. Unique identification | Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this liquid floor. | |
| 2. Designation | Forbo Eurocol 350 LiquidDesign; a permanent flexible liquid floor with a natural and aesthetic appearance. | |
| 3. Application | For creating a permanent flexible liquid floor to an already levelled surface, with a natural and aesthetic appearance. The natural components cork, linseed oil and biopolymer binding agent are renewable and therefore environmentally friendly. | |
| 4. Name and contact address manufacturer | <i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600</i> <i>Email: info.eurocol@forbo.com</i> | |
| 5. Name and contact address authorized | n/a | |
| 6. System of assessment and verification of constancy of performance | 4 | |
| 7. Activity of the notified certification body as required by the harmonized standard | n/a | |
| 8. European Technical Assessment | n/a | |
| 9. Declared performance | In accordance with NEN-EN 13813; Permanent flexible liquid floor, for use inside buildings, to an already levelled surface. | |
| Essential characteristics | Performance | Test method |
| Bond strength | ≥ B1,5 | EN 13892-8:2002 |
| Abrasion resistance | ≤ AR 0,5 | EN 13892-4:2002 |
| Material behaviour in case of fire | | EN 13501-1:2007+A1:2009 |
| Impact resistance | ≥ IR4 | EN-ISO 6272-2:2011 |
| Compressive strength | | NEN-EN 13892-2:2002 |
| Tensile strength | | |
| Surface hardness | NPD | |
| Castor chair resistance | NPD | EN 425:2002 |
| Water permeability | NPD | |
| Shrinkage and swelling | NPD | |
| Consistency | NPD | |
| Modulus of elasticity | ΔLw 5 dB | |
| Sound insulation | NPD | EN-ISO 10140-1-5:2010 en 717-2:2013 |
| Thermal resistance | | |
| Chemical resistance | | |
| Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002 | | |
| 10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4. | | |
| | | Wormerveer, 10-03-2023 signed: ing. T.W. Breeuwer; Manager R&D  |