

888

EUROCLEAN UNI

Universal floorcleaner, clean & care in one step, pH neutral, skin friendly, for all waterproof surfaces, e. g. for linoleum, laminate, Eurocol Surface floors.

PRODUCT TYPING

| | |
|-------------|------------------------------------|
| Base | Water-soluble tensides and scents. |
| Color | Transparent. |
| Consistency | Thin liquid. |

- Wiping water additive for the care and daily maintenance cleaning of resilient floor coverings such as PVC, CV, rubber flooring, linoleum, sealed parquet and cork as well as natural and artificial stone, laminate, Eurocol Surface floors or similar closed surfaces.
- Without layer build-up, the original condition of the floor coverings is maintained in gloss and slip resistance.
- Traces of shoes or soiling are effectively removed.
- The product is low-foaming and can be used as an additive in automatic wipers and for local spray cleaning.
- Makes intensive intermediate cleaning and professional basic cleaning superfluous.
- Skin-friendly, as pH neutral.

PROPERTIES

| | |
|------------------|-----------------------------------|
| Consumption | Depending on degree of dirtiness. |
| Flammability | Non-flammable. |
| Frost resistance | No. |
| Passableness | When the surface is dry. |
| Specific weight | 1.0 kg/l. |

APPLICATION

Wiping water additive for the care and daily maintenance cleaning.

PROCESSING

| | |
|--------------|---|
| Storage | Store cool and free from frost (5°- 30 °C). |
| Tools | Wiper. |
| Mixing ratio | Approx. 40 ml per 8 l wiping water. |
| Waiting time | Dry surface can be walked on. |
| Shelf Life | Minimum 36 Months, in unopened packaging. |
| Cleaner | Water. |
| Remarks | Technical information and safety data sheets of the installation materials and floor coverings/parquet used must be observed. |

888 EUROCLEAN UNI

UBA number: 43970020

Ingredients (according to EU regulation 648-2004):

nonionic surfactants <5%, fragrances (CITRUS DULCIS), preservatives (METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE)

Wear protective gloves / eye protection.

** The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.*

Substrate:

- The sealing of parquet and cork floors must be completely closed.
- Coarse dirt must first be removed by sweeping or vacuuming.

Instruction manual:

Intensive first care (construction cleaning):

Please pour 100 ml (related to the cleaning water) into 1 bucket (8 l) of clean, cold water. Wipe the surface with a damp cloth. Also possible to be used in cleaning machines.

Regular cleaning and maintaining:

Please pour 40 ml into 8 l of clean cold water.

In the case of intensive painting or soiling, leave to take effect briefly and then wipe again.

ENVIRONMENT AND HEALTH

| | |
|----------------------------|---|
| GISCODE | GU50 |
| Safety and environment | Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Material residues can be disposed of as household waste. |
| MSDS | For extensive information about safety and environment we refer to our website www.forbo-eurocol.de . |
| Substances causing allergy | Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. |

ITEM DATA

| artikel | productname | packaging | shipping unit |
|---------|---------------|-------------------|---------------------|
| 888 | Euroclean Uni | PE jerrycan à 5 l | 102/pallet |
| 888 | Euroclean Uni | PE bottle à 1 l | 12/box (on request) |

Any application method/ conditions other than specified in this Technical data sheet require explicit manufacturer's approval. In case of deviance in application method/ conditions liability by manufacturer cannot be guaranteed. This technical data sheet contains advice on handling and application of the product, based on experience and tests run by the manufacturer in laboratory and practical work. The information supplied by the manufacturer are non-binding and cannot be used as a basis for establishing the manufacturers liability for any damages caused. The values stated in this technical data sheet were measured under standard laboratory conditions. As application conditions outside the laboratory vary strongly this technical data sheet must be considered a guide only. Therefore the manufacturer does not take liability for damages caused by the customer's utilization of the technical data sheet content. As use, processing- and storage conditions on site are beyond manufacturers influence, a warranty for the processing result cannot be given. This also includes the infringement of any rights for the protection of third parties. Sufficient testing areas are to be provided before final application. Relevant national norms and regulations of the industry are to be observed. Outside Germany valid, relevant national norms and regulations, have to be taken into account and to be followed by the customer. It is the responsibility of the customer to check product suitability for the intended procedure and purposes prior to use.

This Technical Information supersedes all previously issued application data sheets and product information are no longer valid!

BG175222, Version V08, Stand 2021-06-16, ersetzt Version vom 2015-11-05

888 EUROCLEAN UNI

Forbo Eurocol Nederland B.V. | Industrieweg 1-2 | Postbus 130 | 1520 AC Wormerveer | Tel: +31 (0)75 627 16 00 | info.eurocol@forbo.com
Forbo Eurocol Deutschland GmbH | August-Röbling-Straße 2 | DE - 99091 Erfurt | PF 80 02 53 | Telefon: +49 361 730 41 0 | info.eurocol.de@forbo.com

Eurocol is part of the Forbo Group

