

FOR A CONDUCTIVE INSTALLATION

MANDATORY

523 Eurostar Tack ec

Ref. : 523

523 eurostar tack ec is an electrically conductive, solvent-free PVC adhesive with very low VOC emissions (EMICODE EC1 Plus).

It is recommended for new-build and renovation applications of electrically conductive PVC coverings such as Colorex SD/ EC and Sphera SD/EC.

Technical characteristics :

Waiting time : 10 to 15 minutes

Opening time : 20 minutes

Consumption : 250 g/m² (Spatula S1 recommended)



Bucket of 12 kg

Self-adhesived copper tape

Ref. : 801

For rooms in which a conducting or dissipating floor is necessary. It is used under conducting or dissipating tiles and transfers electrostatic charges to the ground (the connection is made by the electrician).

Installation is done with a conductive adhesive type 523 Eurostar Tack ec.



Roll of 20 m

PROFILE

SUGGESTED

Colorex plus cove former

Ref. : X1197 noir

This profile is used at the foot of the partition.

It allows floorcoverings to be installed with a rounded edge.



Box of one length of 1,22 m

WELDING

MANDATORY

PVC WELDING ROD

Ref. : floorcovering ref

*Sphera welding rods are available in Uni and Multicolor.

Welding allows the junction between strip edges.

Achieves E2/E3 rating with PVC.

A groove is formed, and the weld is then applied using a hot air gun fitted with a PVC fast-welding nozzle.

Coil of 50 m (Sphera)

Coil of 100 m (Colorex)



Estimative consumption of welding rods :

Sheet floorcovering without coving skirting : approx. 0,75 m/m²

Sheet floorcovering with coving skirting : approx. 1 m/m²

Colorex tiles : approx. 3,5 m/m²



Welding rod box number

228 VINYLWELD **Forbo**
↔ 50 m Ø 4 mm # 7712105
433121, 40392

Labelling found on each PVC welding rod

Commercial reference of PVC floorcovering corresponding with this welding rod

SKIRTINGS AND CORNERS

SUGGESTED

Colorex SD/EC/plus skirting

Ref. : 1600 + last 2 numbers of the floor reference

Allow Colorex skirting boards to be installed.

Requires cove former support (Page 1).

Gluing with acrylic or conductive adhesive type 523 Eurostar Tack ec.



Dimensions : Strip height 15cm (10cm on the wall /5cm on the floor) Thickness 2 mm.

Box of 2 lengths of 12,3 m namely 24,6 m/box

Inner /outer preformed corner Colorex SD/EC/plus

Ref. : Inner corner : 1700 + last 2 numbers of the floor reference.

Outer corner : 1800 + last 2 numbers of the floor reference.

To do inner and outer corner.

Gluing with acrylic or conductive adhesive type 523 Eurostar Tack ec.



Dimensions : Strip height 15cm (10cm on the wall / 5cm on the floor) / Thickness 2 mm.

Per unit

Inner /outer preformed corner Sphera EC/SD

Ref. : Inner or outer corner available under the floor reference wish.

Allow the realization of inner and outer corners.

Inner dimension : Height 10 cm (wall) / width 5 cm (floor) / 16 cm of width

Outer dimension : Height 10 cm (wall) / width 5 cm (floor) / 12 cm of width

The installation has to be done with an acrylic adhesive type 522 Eurosafe Tack or 622 Eurostar Tack.

Box of 10 pieces



RAMPS


SUGGESTED

Colorex plus aluminum access ramp

Ref. : R260

For finishing borders by filling in the difference in level between tiles and subfloor.

Facilitates the access of rolling loads.



Box of 10 lengths of 2,7 m namely 27 m/box



Colorex plus ramp access

For finishing borders by filling in the difference in level between tiles and subfloor.

It facilitates access for wheelchairs.



Box of one length of 1,22m.

Maximum thickness : 10.30 mm


Minimum thickness : 2 mm



171504
Montblanc




171505
Adula



171507
Quartz




171513
Sahara



171522
Niagara



171531
Sole



171500
Grise