































Technical specifications

Eternal de luxe meets the requirements of EN ISO 11638



	Total thickness	EN ISO 24346	3.0 mm
	Surface finish		PUR Pearl
	Wear layer thickness	EN ISO 24340	0.70 mm
	Wear layer binder content	EN ISO 10582	Type 1
	Collection size		20
	Domestic use	EN ISO 10874	Class 23
	Commercial use	EN ISO 10874	Class 33
	Light industrial use	EN ISO 10874	Class 42
	Roll width	EN ISO 24341	2.0 m / 4.0 m
	Roll length	EN ISO 24341	≤ 25 m
	Total weight	EN ISO 23997	2700 g/m²
	Dimensional stability	EN ISO 23999	≤ 0.1 %
	Slip resistance (ramp test)	DIN 51130	R10
	Castor chair continuous use	ISO 4918	Pass
	Residual indentation <i>Typical value</i>	EN ISO 24343-1	≤ 0.15 mm ~ 0.10 mm
	Colour fastness to light	EN ISO 105-B02 method 3	≥ 6
	Indoor air emissions: TVOC after 28 days	EN 16516	≤ 0.05 mg/m³
	Acoustical impact noise reduction		17dB
	Resistance to chemicals	EN ISO 26987	Very good
	Flexibility	EN ISO 24344	Ø 10 mm
	Use in wet areas	EN 13553	Yes
	Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact	
	Creating better environments		
	Renewable electricity	Eternal de luxe is manufactured using 100% electricity from renewable sources	
	Recycled content	Eternal de luxe contain up to 18% recycled content by weight	
	Black to the floor	Installation off cuts can be collected via our Back to the Floor scheme	
	SKA	Eternal de Luxe meets the Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
Eternal de luxe meets the requirements of EN 14041:2004			
	Product code	EN 14041	0200403-DoP-306
	Product code	BS EN 14041	0200403-DoP-GB306
	Reaction to fire	EN 13501-1	B _{f1} -s1, L, CS
	Slip resistance	EN 13893	μ ≥ 0.30
	Thermal conductivity	EN 12524	0.25 W/mK
	Body voltage	EN 1815	≤ 2.0 kV



All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001. All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001. The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

Registered office:
Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England 9200318

London EC1 showroom
79 St John Street, Clerkenwell
London EC1M 4NR
Tel: 0207 553 9300

For commercial enquiries
If calling from the North,
London & South East
Tel: 0800 0282 162
If calling from
Scotland, Midlands & South West
Tel: 0800 0935 258

Nuway enquiries:
Tel: 01773 740 688
Residential enquiries:
Tel: 0800 0935 846
E-mail: info.flooring.uk@forbo.com
www.forbo-flooring.co.uk

Ireland
Forbo Ireland Ltd
2 Deansgrange Business Park Blackrock
Co Dublin
Tel: 00353 1 2898 898
Email: info.ireland@forbo.com
www.forbo-flooring.ie

Find us on



NBS Source
Manufacturing Partner



SAMPLE SERVICE
0800 731 2369
samples.uk@forbo.com



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.



creating better environments

FLOORING SYSTEMS