

Page 1/9

Revision: 22.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 7 (replaces version 6)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 650 Eurostar Fastcol

· Article number: 650

• 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / preparation Contact adhesive

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Forbo Eurocol Nederland B.V.

Industrieweg 1-2

NL-1521 NA Wormerveer Holland

Tel. +31 75 6271600 - Fax +31 75 6283564 E-mail address: info.eurocol@forbo.com

Website: www.eurocol.com

· 1.4 Emergency telephone number:

In case of emergency please contact the Dutch National Poison Control, telephone number: 0031-(0)88-755 8000 (This number is only accessible to the physician treating the patient and only in case of accidental poisoning).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:

Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

GE

Printing date 22.11.2022

Version number 7 (replaces version 6)

Trade name: 650 Eurostar Fastcol

(Contd. of page 1)

Revision: 22.11.2022

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Contact adhesive based on polymer dispersions and additives.

, , , ,		
Dangerous compon	nents:	
EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<1%
CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 1, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<1%
	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ♠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ♠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: $C \ge 0.6$ % Skin Irrit. 2; H315: 0.06 % ≤ $C < 0.6$ % Eye Dam. 1; H318: $C \ge 0.6$ % Skin Sens. 1A; H317: $C \ge 0.0015$ %	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Not applicable.
- · After skin contact: Wash with water and soap.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a physician.

- · After swallowing: Rinse mouth with water and consult physician immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 22.11.2022 Version number 7 (replaces version 6) Revision: 22.11.2022

Trade name: 650 Eurostar Fastcol

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect product in waste container. Rinse floor with water.

6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool, but frost-proof location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Recommended storage temperature between 15 and 25 ℃.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs		
2634-33-5	1,2-benzisothiazol-3(2H)-one	
Dermal	DNEL long term	0.966 mg/kg KG/d (wrk)
	DNEL short term systemic health problems	0.345 mg/kg/d (Consumer)
Inhalative	DNEL Inhalative long terme	1.2 /mg/m³ (Consumer)
	DNEL	6.81 mg/m³ (wrk)
55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
Oral	DNEL	0.09 mg/kg (Consumer)
		(Country on many)

(Contd. on page 4)

Revision: 22.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 7 (replaces version 6)

Trade name: 650 Eurostar Fastcol

		(Contd. of page 3)	
Inhalative DNEL Inhalative long terme 0.02 /mg/m³ (Consumer)		0.02 /mg/m³ (Consumer)	
·PNECs			
2634-33-5 1,2	2-benzisothiazol-3(2H)-one		
PNEC	4.99 μg/kg (Sea Water Sediment)		
	49.9 μg/kg (Fresh Water Sediment)		
PNEC ug/l	0.403 μg/l (Sea Water)		
	4.03 μg/l (Fresh Water)		
PNEC mg/kg	3 mg/kg (Soil)		
	55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)		
PNEC mg/kg 0.01 mg/kg (Soil)			
	0.027 mg/kg (Sea Water Sediment)		
	0.027 mg/kg (Fresh Water Sediment)		

- · Additional information: The lists valid during manufacture were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material is dependant on the penetration times, rates of diffusion and degradation.

Material of gloves

Suitable chemical-resistant gloves (EN 374) even with longer direct contact (recommendation: protection index 6, corresponding> 480 minutes permeation time (permeation) according to EN 374) e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) and others. Due to several factors that can influence (e.g. temperature), it must be taken into account that the service life of a chemical glove can in practice be considerably shorter than the permeation time indicated by the test.

- Penetration time of glove material > 480 Minutes.
- · For prolonged contact gloves made of the following materials are suitable:

Chloroprene and butylrubber.

Nitrile rubber

· Eye/face protection Goggles recommended during refilling

GB

Printing date 22.11.2022 Version number 7 (replaces version 6) Revision: 22.11.2022

Trade name: 650 Eurostar Fastcol

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- General Information

Colour: Cream coloured
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 100 ℃

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: Not applicable.
 Decomposition temperature: Not determined.

· pH at 20 °C 7

Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 23 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Paste

· Important information on protection of health and environment, and on safety.

• Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Solvent content:

· Organic solvents: 0.0 % · VOC(EC%) 0.0 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives

Explosives

Flammable gases

Oxidi
Oxidising gases

Void
Gases under pressure

Flammable liquids

Flammable solids

Void

Void

(Contd. on page 6)

Printing date 22.11.2022 Version number 7 (replaces version 6) Revision: 22.11.2022

Trade name: 650 Eurostar Fastcol

		(Contd. of page 5)
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamn	nable	
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	64-66 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rat)

- · Skin corrosion/irritation Possible irritation with prolonged or frequent contact.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

Printing date 22.11.2022

Version number 7 (replaces version 6)

Trade name: 650 Eurostar Fastcol

(Contd. of page 6)

Revision: 22.11.2022

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic to	· Aquatic toxicity:		
2634-33-5	1,2-benzisothiazol-3(2H)-one		
EC50/3h	13 mg/l (Not specified)		
2682-20-4	2682-20-4 2-methyl-2H-isothiazol-3-one		
EC50/3h	34.6 mg/l (activated sludge)		
EC 20/3 H	2.8 mg/l (activated sludge)		
55965-84-9	55965-84-9 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
LC50/96h	0.28 mg/l (LM)		
	0.188 mg/l (OM)		
EC50/48 h	0.126 mg/l (DM)		

12.2 Persistence and degradability

2682-20-4 2-methyl-2H-isothiazol-3-one

OECD 308 Simulation Biodegradation Agu Sed System 1.28-2.1 days (Not specified)
OECD 307 Aerobic and Anaerobic Transfortmation Soi <0.08 days (Not specified)
OECD 309 Simulation Biodegradation Surface Water 4.1 days (Not specified)

· 12.3 Bioaccumulative potential

2682-20-4 2-methyl-2H-isothiazol-3-one

BCF 3.16 BCF (Not specified)

Verdelingscoëfficient n-octanol/water ≤0.32 [---] (log Pow) (Not specified)

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Do not allow large quantities to reach sewage system or surface water.

According to the criteria of the EU-classification and labelling "dangerous for environment" (93/21/EWG) the substance/ the product has to be classified as non-hazardous for the environment.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.

(Contd. on page 8)

Printing date 22.11.2022

Version number 7 (replaces version 6)

Trade name: 650 Eurostar Fastcol

(Contd. of page 7)

Revision: 22.11.2022

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Warm water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMC instruments	Not applicable.
·Transport/Additional information:	Not classified as hazardous under transport regulations.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin.

(Contd. on page 9)

Revision: 22.11.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 7 (replaces version 6)

Trade name: 650 Eurostar Fastcol

(Contd. of page 8) H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. Department issuing SDS: R&D department · Contact: Ing. T.W. Breeuwer · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB