

eurocol

530

the strong connection

27-6-2026



EUROSAFE CORK

Fast-setting floor covering adhesive with a short waiting time for gluing carpet, wall tapestry, linoleum, bulletin board and cork tiles on walls and floors. The substrate must be absolutely permanently dry. Thanks to EMICODE EC 1PLUS (very low emission) also suitable for BREEAM projects.

PRODUCT TYPING

Base	Sulphite lye and fillers dispersed in water.
Color	Brown.
Consistency	Thick liquid.

- Very low emission
- Emicode EC 1PLUS
- Non-flammable
- Easy and safe to apply
- High initial adhesion strength

PROPERTIES

Consumption	550 - 650 g/m ² .
Flammability	Non-flammable.
Sensitive to frost	Yes.
Humidity resistance	When dry 530 Eurosafe Cork is not moisture-resistant.
Specific weight	1.66 kg/l.

APPLICATION

For installing on permanently dry subfloors of:

- linoleum
- carpet
- wall carpet
- cork wall and floor tiles
- bulletin board.

PROCESSING

Storage	Store cool and free from frost.
Tools	Eurocol spreader no. 850/B1.
Curing	24 hours.*

530 EUROSAFE CORK

Open time	10-15 minutes.*
Waiting time	None.
Moisture resistance	When dry 530 Eurosafe Cork is not moisture-resistant.
Shelf Life	15 months, in unopened packaging.
Cleaner	Water.

*The stated values are laboratory values which, given the large variation in climatological conditions, subfloor compositions and layer thicknesses, are only guideline values.

Substrate:

- 530 Eurosafe Cork is suitable for any type of subfloor that has a good tensile and compression strength. The subfloor should also be even, clean, permanently dry and free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.
- Only use pervious floor coverings on impervious subfloors.
- When installing impervious floor coverings on impervious subfloors apply a 2 mm levelling compound layer.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

Instruction manual:

- Apply the adhesive with a regular notched adhesive spreader (Eurocol spreader no. 850/B1).
- Place the material directly into the wet adhesive and roll and/or press thoroughly.
- Remove fresh adhesive spots immediately with water.

Working conditions:

Required surrounding temperature : 18 - 23 °C.
 Temperature for material and subfloor : min. 15° - max. 20 °C.
 Relative humidity : 40 - 80%.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1) and benzisothiazolinone. May produce an allergic reaction.

QUALITY AND GUARANTEE



ENVIRONMENT AND HEALTH

Hazard Class	None.
Safety and environment	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155. Keep out of reach of children. Do not eat, drink or smoke while processing the product. Only give completely empty containers for recycling. Bound material residues can be disposed of as household waste.
MSDS	For extensive information about safety and environment we refer to our website www.eurocol.nl .

ITEM DATA

Article	Definition	Packaging	EAN-code
530	Eurosafe Cork	13.5 kg Bucket	8 710345 483506

530 EUROSAFE CORK